

## WP STRIP 45

**2-layer** 11mm with approx. 4,5 mm wear layer  
Dimension: 360 x 108 x 11 mm

Installation method



### Functionalities:



**MAINTENANCE FREE-PARQUET:** For residential use the complicated and time consuming maintenance is no longer required.



**HEALTHY-PARQUET:** Creates a sense of well being and healthy living that helps restrict/reduce/remove allergens from the environment of the potential allergy sufferer.



**SOUND REDUCTION-PARQUET:** Created to help reduce transmitted sound within a room.

### Laying patterns:



### Description of the product:

Total thickness	2-layer construction 11mm
Wear layer	4.5 mm wear layer
Bottom layer material	HDF (High Density Fiberboard)
Treatment	strip parquet block, 4-sided tongue and groove
Moisture content	long seasoned and technically dried wood (moisture content 8 % ± 1 %)
Composition	92% of renewable raw material, 7% of combined water and 1-2% of emission-free synthetic material
Under-floor heating	Oak ideally suitable, Mountain Maple only limited suitable.
Fire resistance	C <sub>fl</sub> -s1 (hardly inflammable) – Please pay attention to the conditions for installation

Species/Colours/Grading/Additional Treatments  
See price list 2013

Ecological Responsibility



### Surfaces:



**PROSTRONG – LACQUERED SURFACE FINISH**

Pre-finished lacquered sealing, maintenance-free, consisting of 7 matched eco friendly layers in a satin gloss optical appearance. Combines antistatic and antibacterial qualities. Meets Class C of ONORM C 2354 (the highest standard for anti scratch resistance). Resistance against chemicals according to EN 13442. Exceeds 12 times the requirements of the chair-rollers test according to EN 425. Slide inhibition class R10 of DIN 51130.



**PROACTIVE+ – THE NATURAL MATT SURFACE FINISH**

Combines the advantages of the ProStrong surface finish with the appearance of the natural Oiled finish ProVital. Meets Class C of ONORM C 2354 (the highest standard for anti scratch and resistance against certain chemicals etc). Combines antistatic and antibacterial qualities. Meets the requirements of the chair-rollers test according to EN 425. Slide inhibition class R10 of DIN 51130.



**PROVITAL finish – THE NATURAL OILED SURFACE FINISH**

100% natural surface finish consisting of Sunflower, Thistle and Soya Oil as well as Candellila Wax, sealing the open pores. Local renovation is possible. For installation in residential areas no further application of PVFinish is necessary. In case of installation in areas with high wear and tear (e.g. public buildings, restaurants...) an additional application of PVFinish is mandatory. Slide inhibition class R9 of DIN 51130.

### Intelligent Characteristics:

- Especially long lasting due to 4.5 mm wear layer
- Unique design possibilities